



**UNITED STATES PATENT AND TRADEMARK OFFICE**

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER OF PATENTS AND TRADEMARKS  
Washington, D.C. 20231  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/496,600	02/02/2000	Hang Zhang	50325-109	6479

7590                    04/08/2003

CHRISTOPHER J. PALERMO  
HICKMAN PALERMO TRUONG & BECKER LLP  
1600 WILLOW STREET  
SAN JOSE, CA 95125-5106

[REDACTED] EXAMINER

BOUTAH, ALINA A

[REDACTED] ART UNIT

[REDACTED] PAPER NUMBER

2143

DATE MAILED: 04/08/2003

12

Please find below and/or attached an Office communication concerning this application or proceeding.

<b>Office Action Summary</b>	<b>Application No.</b>	<b>Applicant(s)</b>	
	09/496,600	ZHANG ET AL.	
	<b>Examiner</b>	<b>Art Unit</b>	
	Alina N Boutah	2143	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

#### Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
- Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

#### Status

1) Responsive to communication(s) filed on 26 March 2003.

2a) This action is FINAL.                    2b) This action is non-final.

3) Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

#### Disposition of Claims

4) Claim(s) 1-24 is/are pending in the application.

4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.

5) Claim(s) \_\_\_\_\_ is/are allowed.

6) Claim(s) \_\_\_\_\_ is/are rejected.

7) Claim(s) \_\_\_\_\_ is/are objected to.

8) Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

#### Application Papers

9) The specification is objected to by the Examiner.

10) The drawing(s) filed on \_\_\_\_\_ is/are: a) accepted or b) objected to by the Examiner.

Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

11) The proposed drawing correction filed on 02 January 2003 is: a) approved b) disapproved by the Examiner.

If approved, corrected drawings are required in reply to this Office action.

12) The oath or declaration is objected to by the Examiner.

#### Priority under 35 U.S.C. §§ 119 and 120

13) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

a) All b) Some \* c) None of:

1. Certified copies of the priority documents have been received.
2. Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

14) Acknowledgment is made of a claim for domestic priority under 35 U.S.C. § 119(e) (to a provisional application).

a) The translation of the foreign language provisional application has been received.

15) Acknowledgment is made of a claim for domestic priority under 35 U.S.C. §§ 120 and/or 121.

#### Attachment(s)

1) <input type="checkbox"/> Notice of References Cited (PTO-892)	4) <input type="checkbox"/> Interview Summary (PTO-413) Paper No(s). _____.
2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948)	5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152)
3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449) Paper No(s) _____.	6) <input type="checkbox"/> Other: _____

**DETAILED ACTION**

***Response to Amendment***

Claims 1-24 are pending in this application. Claims 1, 11, 17, 23 and 24 are amended.

***Response to Arguments***

Applicant's arguments with respect to claims 1-24 have been considered but are moot in view of the new ground(s) of rejection.

***Drawings***

The drawings are objected to under 37 CFR 1.83(a). The drawings must show every feature of the invention specified in the claims. Therefore, the "HTML daemon" specified in claims 6, 16, and 22 must be shown or the feature(s) canceled from the claim(s). No new matter should be entered.

A proposed drawing correction or corrected drawings are required in reply to the Office action to avoid abandonment of the application. The objection to the drawings will not be held in abeyance.

***Claim Rejections - 35 USC § 102***

The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

Art Unit: 2143

(e) the invention was described in a patent granted on an application for patent by another filed in the United States before the invention thereof by the applicant for patent, or on an international application by another who has fulfilled the requirements of paragraphs (1), (2), and (4) of section 371(c) of this title before the invention thereof by the applicant for patent.

The changes made to 35 U.S.C. 102(e) by the American Inventors Protection Act of 1999 (AIPA) do not apply to the examination of this application as the application being examined was not (1) filed on or after November 29, 2000, or (2) voluntarily published under 35 U.S.C. 122(b). Therefore, this application is examined under 35 U.S.C. 102(e) prior to the amendment by the AIPA (pre-AIPA 35 U.S.C. 102(e)).

Claims 1- 24 are rejected under 35 U.S.C. 102(e) as being anticipated by USPN 6,389,464 issued to Krishnamurthy et al.

(Amended) Regarding claim 1, Krishnamurthy et al. teach a method for obtaining a current value of a Management Information Base (MIB) variable stored in a managed network device in a network, the method comprising the steps of:

receiving a connection of a Web browser to the network device (column 7, lines 54-65);  
receiving at the network device an HTTP request message from the browser to obtain the current value of the MIB variable (column 8, lines 62 – column 9, lines 1-54);  
receiving the current value of the MIB variable from the MIB of the network device (column 7, lines 66-67 – column 8 lines 1-15); and  
communicating the current value of the MIB variable from the network device to the browser using an HTTP reply message (column 10, lines 48-54; figures 25-27).

Regarding claim 2, Krishnamurthy et al. teach the method of claim 1, further comprising the steps of:

creating and storing a MIB object tree in a memory of the network device (column 19, lines 48-54; column 20, lines 49-57);  
creating an electronic document that contains a representation of one or more MIB variables of the MIB object tree (figures 25-27);  
communicating the electronic document to the Web browser (figures 25-27).

Regarding claim 3, Krishnamurthy et al. teach the method of claim 1, wherein the step of receiving the current value of the MIB variable from the MIB of the network device includes the steps of creating and storing a MIB object tree in a memory of the network device (column 19, lines 48-54; column 20, lines 49-57); obtaining the MIB variable from the MIB object tree in the memory of the network device (column 10, lines 63-67 – column 11, lines 1-8).

Regarding claim 4, Krishnamurthy et al. teach the method of claim 1, further comprising the steps of:

creating and storing a MIB object tree in a memory of the network device (column 19, lines 48-54; column 20, lines 49-57);  
creating an electronic document that contains a representation of one or more MIB variables of the MIB object tree (figures 25-27);  
receiving a user selection of one of the MIB variables based on the electronic document (102 figure 4; figures 25-27; column 7, lines 54-65);

wherein the step of receiving the current value of the MIB variable from the MIB of the network device includes the step of obtaining the MIB variable that is identified in the user selection from the MIB object tree in the memory of the network device (figures 25-26).

Regarding claim 5, Krishnamurthy et al. teach the method of claim 1, further comprising: receiving the HTTP request message to obtain the current value of the MIB variable at an HTTP-SNMP interface (col. 3, lines 16-33; col. 4, lines 7-11; col. 7, lines 54-65); creating an SNMP query that requests a current value of the MIB variable based on the HTTP request message (column 7, lines 54-65; column 8, lines 62-67 – column 9, lines 1-8); and communicating the SNMP query to an SNMP daemon of the network device (column 7, lines 66-67 – column 8 lines 1-15; column 8, lines 62 – column 9, lines 1-54).

Regarding claim 6, Krishnamurthy et al. teach the method of claim 1, further comprising the steps of:

communicating the current value of the MIB variable to the HTTP-SNMP interface (col. 3, lines 16-33; col. 4, lines 7-11; col. 7, lines 54-65); creating and storing an HTML page that contains the current value of the MIB variable (col. 4, lines 43-53; col. 6, lines 36-44); and sending the HTML page to an HTML daemon of the network device (col. 7, lines 54-65).

Regarding claim 7, Krishnamurthy et al. teach the method of claim 1, further comprising the step of creating and storing an executable software element in association with the Web

browser, wherein the executable software element is configured for packaging an SNMP query into the request from the Web browser (column 2, lines 24-55, column 8, lines 24-47).

Regarding claim 8, although Krishnamurthy et al. do not explicitly disclose the method of claim 1, wherein the step of receiving a request from the Web browser to obtain the current value of the MIB variable includes the step of unpackaging an SNMP query that is packaged in the request from the Web browser to identify the MIB variable, by the principle of inherency, in order for obtain the current value of the MIB, the SNMP request must be packaged and unpackaged at the web browser.

Regarding claim 9, Krishnamurthy et al. teach the method of claim 8, further comprising the step of sending the SNMP query to an SNMP daemon of the network device (column 7, lines 66-67 – column 8 lines 1-15; column 8, lines 62 – column 9, lines 1-54).

Regarding claim 10, although Krishnamurthy et al. do not explicitly disclose the method of claim 8, wherein the step of returning the current value of the MIB variable to the Web browser includes the step of repackaging the current value of the MIB variable into an HTTP reply message, by the principle of inherency, in order for the web browser to receive the current value of the MIB, it must be repackaged in the reply message.

(Amended) Regarding claim 11, Krishnamurthy et al. teach a network device, comprising:

Art Unit: 2143

a processor (column 19 line 63);

a Management Information Base (MIB) logically accessible by the processor and comprising one or more stored values of MIB variables (column 19, lines 63-67 – column 20, lines 1-8);

a Simple Network Management Protocol (SNMP) daemon executed by the processor (column 2, lines 24-55);

a Hypertext Transfer Protocol (HTTP) daemon executed by the processor (column 7, lines 54-65);

stored instructions for obtaining a current value of a Management Information Base (MIB) variable stored in a managed network device which, when executed by the processor, cause the processor to carry out the steps of:

receiving a connection of a Web browser at the HTTP daemon to the network device (column 7, lines 54-65);

receiving at the network device an HTTP request message from the browser to obtain the current value of one of the MIB variable (column 8, lines 54-56);

receiving the current value of the MIB variable from the MIB of the network device (column 7, lines 66-67 – column 8 lines 1-15; column 8, lines 62 – column 9, lines 1-54); and

communicating the current value of the MIB variable from the network device to the browser using an HTTP reply message (column 10, lines 48-54; figures 25-27).

Regarding claim 12, Krishnamurthy et al. teach the network device of claim 11, wherein the instructions further cause the processor to carry out the steps of:

Art Unit: 2143

creating and storing a MIB object tree in a memory of the network device (column 19, lines 48-54; column 20, lines 49-57);

creating an electronic document that contains a representation of one or more MIB variables of the MIB object tree (figures 25-27);

communicating the electronic document to the Web browser (figures 25-27).

Regarding claim 13, Krishnamurthy et al. teach the network device of claim 11, wherein the step of receiving the current value of the MIB variable from the MIB of the network device includes the steps of creating and storing a MIB object tree in a memory of the network device (column 19, lines 48-54; column 20, lines 49-57); obtaining the MIB variable from the MIB object tree in the memory of the network device (column 10, lines 63-67 – column 11, lines 1-8).

Regarding claim 14, Krishnamurthy et al. teach the network device of claim 11, wherein the instructions further cause the processor to carry out the steps of:

creating and storing a MIB object tree in a memory of the network device (column 19, lines 48-54; column 20, lines 49-57);

creating an electronic document that contains a representation of one or more MIB variables of the MIB object tree (figures 25-27);

receiving a user selection of one of the MIB variables based on the electronic document (102 figure 4; figures 25-27; column 7, lines 54-65);

wherein the step of receiving the current value of the MIB variable from the MIB of the network device includes the step of obtaining the MIB variable that is identified in the user selection from the MIB object tree in the memory of the network device (figures 25-26).

Regarding claim 15, Krishnamurthy et al. teach the method of claim 11, further comprising an HTTP-SNMP interface which, when executed by the processor, causes the processor to carry out to steps of:

receiving the HTTP request message to obtain the current value of the MIB variable at an HTTP-SNMP interface (col. 3, lines 16-33; col. 4, lines 7-11; col. 7, lines 54-65);  
creating an SNMP query that requests a current value of the MIB variable based on the HTTP request message (column 7, lines 54-65; column 8, lines 62-67 – column 9, lines 1-8); and  
communicating the SNMP query to an SNMP daemon of the network device (column 7, lines 66-67 – column 8 lines 1-15; column 8, lines 62 – column 9, lines 1-54).

Regarding claim 16, Krishnamurthy et al. teach the network device of claim 11, further comprising the steps of:

communicating the current value of the MIB variable to the HTTP-SNMP interface (col. 3, lines 16-33; col. 4, lines 7-11; col. 7, lines 54-65);  
creating and storing an HTML page that contains the current value of the MIB variable (col. 4, lines 43-53; col. 6, lines 36-44); and  
sending the HTML page to an HTML daemon of the network device (col. 7, lines 54-65).

(Amended) Regarding claim 17, Krishnamurthy et al. teach a computer-readable medium carrying one or more sequences of one or more instructions for obtaining a current value of a Management Information Base (MIB) variable stored in a managed network device in a network, the one or more sequences of one or more instructions including instructions which, when executed by one or more processors, cause the one or more processors to perform the steps of:

receiving a connection of a Web browser to the network device (column 7, lines 54-65);

receiving at the network device an HTTP request message from the browser to obtain the current value of

the MIB variable (column 8, lines 62 – column 9, lines 1-54);

receiving the current value of the MIB variable from the MIB of the network device (column 7, lines 66-67 – column 8 lines 1-15); and

communicating the current value of the MIB variable from the network device to the browser using an HTTP reply message (column 10, lines 48-54; figures 25-27).

Regarding claim 18, Krishnamurthy et al. teach the computer-readable medium as recited in claim 17, wherein the instructions further cause the processor to carry out the steps of creating and storing a MIB object tree (column 19, lines 48-54; column 20, lines 49-57);

creating an electronic document that contains a representation of one or more MIB variables of the MIB object tree (figures 25-27);

communicating the electronic document to the Web browser (figures 25-27).

Regarding claim 19, Krishnamurthy et al. teach the computer-readable medium as recited in claim 17, wherein receiving the current value of the MIB variable from the MIB of the network device includes the steps of creating and storing a MIB object tree in a memory of the network device (column 19, lines 48-54; column 20, lines 49-57); obtaining the MIB variable from the MIB object tree in the memory of the network device (column 10, lines 63-67 – column 11, lines 1-8).

Regarding claim 20, Krishnamurthy et al. teach the computer-readable medium as recited in claim 17, wherein the instructions further cause the processor to carry out the steps of:

creating and storing a MIB object tree in a memory of the network device (column 19, lines 48-54; column 20, lines 49-57);

creating an electronic document that contains a representation of one or more MIB variables of the MIB object tree (figures 25-27);

receiving a user selection of one of the MIB variables based on the electronic document (102 figure 4; figures 25-27; column 7, lines 54-65);

wherein receiving the current value of the MIB variable from the MIB of the network device includes the step of obtaining the MIB variable that is identified in the user selection from the MIB object tree in the memory of the network device (figures 25-26).

Regarding claim 21, Krishnamurthy et al. teach the computer-readable medium as recited in claim 17, wherein the instructions further cause the processor to carry out the steps of:

Art Unit: 2143

receiving the HTTP request message to obtain the current value of the MIB variable at an HTTP-SNMP interface (col. 3, lines 16-33; col. 4, lines 7-11; col. 7, lines 54-65); creating an SNMP query that requests a current value of the MIB variable based on the HTTP request message (column 7, lines 54-65; column 8, lines 62-67 – column 9, lines 1-8); and communicating the SNMP query to an SNMP daemon of the network device (column 7, lines 66-67 – column 8 lines 1-15; column 8, lines 62 – column 9, lines 1-54).

Regarding claim 22, Krishnamurthy et al. teach the computer-readable medium as recited in claim 17, wherein the instructions further cause the processor to carry out the steps of:

communicating the current value of the MIB variable to the HTTP-SNMP interface (col. 3, lines 16-33; col. 4, lines 7-11; col. 7, lines 54-65); creating and storing an HTML page that contains the current value of the MIB variable (col. 4, lines 43-53; col. 6, lines 36-44); and sending the HTML page to an HTML daemon of the network device (col. 7, lines 54-65).

(Amended) Regarding claim 23, Krishnamurthy et al. teach an HTTP browser program including a plug-in executable software element configured for obtaining a current value of a Management Information Base (MIB) variable stored in a managed network device in a network and which, when executed by a processor that executes the browser, causes the processor to carry out the steps of:

receiving a connection of a web browser to the network device (column 7, lines 54-65);

receiving at the network device an HTTP request message from the browser to obtain the current value of the MIB variable (column 8, lines 62 – column 9, lines 1-54);  
receiving the current value of the MIB variable from the MIB of the network device  
(column 7, lines 66-67 – column 8 lines 1-15); and  
communicating the a current value of the MIB variable from the network device to the browser using an HTTP reply message (column 8, lines 62 – column 9, lines 1-54; column 10, lines 48-54; figures 25-27).

(Amended) Regarding claim 24, Krishnamurthy et al. teach an applet executable in a browser program and configured for obtaining a current value of a Management Information Base (MIB) variable stored in a managed network device in a network and which, when executed by the browser, causes the browser to carry out the steps of:

receiving a connection of a Web browser to the network device (column 7, lines 54-65);  
receiving at the network device an HTTP request message from the browser to obtain current value of the MIB variable (column 8, lines 62 – column 9, lines 1-54);  
receiving the current value of the MIB variable from the MIB of the network device  
(column 7, lines 66-67 – column 8 lines 1-15); and  
communicating the current value of the MIB variable from the network device to the browser using an HTTP reply message (column 8, lines 62 – column 9, lines 1-54; column 10, lines 48-54; figures 25-27).

Art Unit: 2143

***Conclusion***


Any inquiry concerning this communication or earlier communications from the examiner should be directed to Alina N Boutah whose telephone number is (703) 305-5104. The examiner can normally be reached on Monday-Friday (8:30 am-5:30 pm).

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, David A Wiley can be reached on (703) 308-5221. The fax phone numbers for the organization where this application or proceeding is assigned are (703) 746-9112 for regular communications and (703) 305-3718 for After Final communications.

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the receptionist whose telephone number is (703) 305-3900.

ANB

ANB  
April 6, 2003



DAVID WILEY  
SUPERVISORY PATENT EXAMINER  
TECHNOLOGY CENTER 2100